

## Monitors

NVM-617LCD, NVM-619LCD



### Key Features

- Dedicated to permanent operation (24/7)
- LED backlight
- Glass shield protecting LCD panel
- Function preventing from burning-in static images on the LCD panel
- Convenient access to connectors
- Installation on the wall without additional brackets

### Dimensions



	NVM-617LCD	NVM-619LCD
<b>MATRIX</b>		
Type	TFT, LED backlight	
Screen Size (Diagonal)	17" (431 mm)	19" (482.6 mm)
	1280x1024	
Viewable Size	337.9 mm x 270.3 mm	376.3 mm x 301.1 mm
Format	4:3	
Brightness	250 cd/m <sup>2</sup>	
Contrast Ratio	1000:1	
Viewing Angle (L/R/T/B)	85°/85°/80°/80°	
Response Time	5 ms	
Display Color	16.7 mln	
<b>OTHER FUNCTIONS</b>		
OSD	Polish, English, Russian and others	
Built-in Speakers	2 x 1 W	
Digital Filter	3D	
<b>INTERFACE</b>		
Video Input	2 x CVBS, BNC connector (loop-through) 1 x VGA 1 x S-Video 1 x HDMI	
Audio Input	1 x Jack stereo (loop-through)	
<b>INSTALLATION PARAMETERS</b>		
Dimensions (mm)	376 (H) x 371 (W) x 197 (D)	423 (H) x 419 (W) x 197 (D)
Weight	4.5 kg	5.2 kg
Case	Black, plastic, glass shield protecting LCD panel	
Power Supply	12 VDC (100 ~ 240 VAC/12 VDC PSU in-set included)	
Power Consumption	25 W	27 W
Operating Temperature	0°C ~ 40°C	
Mounting Standard	VESA 100 x 100 mm	