



Data approve	Product	Proximity Sensor	Date	2025/03/21
	Series	PM08 Series	Issuer	QC-Dept.
Model	型號	PM08-02XE-PG		
Operating voltag	工作電壓	10 ~ 30VDC		
Ripple of power	電源漣波	20% peak to peak		
Current consumption	耗電流	10mA max.		
Sensing distance	檢測距離	2.0mm		
Hysteresis	應差	10% of sensing distance max.		
Response frequency	響應頻率	2500Hz min.		
Output method	輸出方式	NPN & PNP two output NO/NC CHANGEABLE		
Output status	輸出狀態	NO/NC		
Output current	輸出電流	150mA max.		
Residual voltage	殘留電壓	0.1V max.		
Leakage current	洩漏電流	0.8mA max.		
Protection circuit	保護電路	Short circuit & polarity reversed protection		
Dielectric strength	耐電壓強度	2.5kv / 1 minute min.		
Insulation strength	絕緣強度	100 MΩ / 500vdc		
Operating circumstanc	工作環境	-20℃ ~ +80℃ ; 35% ~ 85% RH		
Protection class	保護等級	IP-67		
EMC 標準		ESD : 8kv air charge (level 3) / EN-61000-4-2 Burst test : 2kv / EN61000-4-4 RF interference : 10V / M / ENV-50140		

Output circuit / 接線圖	Outline Dimension/外型尺寸圖				
 Combinación de conexiones de sensores inductivos FOTEK <table border="1"> <tr> <td>1er PNP N/C</td> <td>2do NPN N/C</td> </tr> <tr> <td>1er PNP N/O</td> <td>2do NPN N/O</td> </tr> </table>	1er PNP N/C	2do NPN N/C	1er PNP N/O	2do NPN N/O	 PM-08-02XE-PG
1er PNP N/C	2do NPN N/C				
1er PNP N/O	2do NPN N/O				

發行章		品管部	
-----	---	-----	---